

Product Specifications



P181129

AIR FILTER, PRIMARY ROUND

Why Choose Donaldson Air Filters?

Strong, pliable gasket is compressed against the air cleaner housing to create a tight seal.

- High-efficiency cellulose media performs across a wide range of heavy-duty engine applications.
- Corrosion resistant, coated steel liners support media during operation and help maximize airflow.
- Pleatloc™ feature ensures uniform pleat spacing and prevents media from bunching to promote longer service life.

Attributes

Outer Diameter	174 mm (6.85 inch)
Inner Diameter	108 mm (4.25 inch)
Length	305 mm (12.01 inch)
Overall Length	318 mm (12.52 inch)
Bolt Hole Diameter	17 mm (0.67 inch)
Efficiency	99.9
Efficiency Test Std	ISO 5011
Туре	Primary

Style	Round
Media Type	Cellulose
Price Type	F
Packaged Dimensions	
Packaged Length	7.3 IN
Packaged Width	7.5 IN
Packaged Height	15.2IN
Packaged Weight	2.4 LB
Packaged Volume	0.4816 FT3
Pieces Per Pallet	108
Pieces Per Box	1

Other Information

Country of Origin	Australia
NMFC Code	069100-06
HTS Code	8421310052
UPC Code	742330026151

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.