

P566412

HYDRAULIC FILTER, CARTRIDGE DT



Why Choose Donaldson DT Filters

High-performance DT Hydraulic Cartridges utilize Donaldson Synteq™ media technology which extends filter life, allows a higher initial cleanliness, and provides superior hydraulic system protection.

- DT hydraulic filters help protect equipment, reduce maintenance cost and increase equipment uptime □ which has a direct impact on your bottom line.
- DT filters offer the best available chemical resistance for hydraulic applications.
- A high dirt holding capacity provides longer filter life □ for extended filter change intervals, reducing time and expense for servicing equipment
- Fluorocarbon seals are standard on all Donaldson DT filters.

Attributes

Seal Material	Viton
Outer Diameter	97.5 mm (3.84 inch)
Inner Diameter	40.2 mm (1.58 inch)
Overall Length	233.9 mm (9.21 inch)
Efficiency Beta 1000	5 micron
Collapse Burst	207 bar (3002 psi)

Flow Direction	Outside-In
Style	Cartridge
Series	W451
Brand	DT High-Performance
Media Type	Synthetic
Price Type	FH

Packaged Dimensions

Packaged Length	106.68 mm (4.20 inch)
Packaged Width	106.68 mm (4.20 inch)
Packaged Height	251.46 mm (9.90 inch)
Packaged Weight	1.73 kg (3.80 lb)
Packaged Volume	2862833.19 mm ³ (0.10 ft ³)
Pieces Per Box	1

Other Information

Country of Origin	Canada
NMFC Code	069100-10
HTS Code	8421299013
UPC Code	742330177013

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

accompanies the goods.